



# DX

Ø54 - 26°



anodized  
aluminium



anodized  
bronze

Projector suitable for solid surfaces, wall or ceiling installation. Turned anodized aluminium

available in two sizes ø38mm and different height Sizes (h.60mm, h.160mm, h.500mm) or ø54mm and different height sizes (h.70mm, h.170mm, h.510mm) extremely versatile due to adjustability and low luminance.

Natural aluminium, Bronze and black (for accessories only) surface anodizing treatment.

Tempered silkscreened transparent glass, mechanically fixed with silicon glue, aluminium

Honeycomb.

Beams DX38 (18°;36°) DX54 (26°;52°)

Supply 24V remote power supply to be ordered, model DX54 also available operating 220-240V.

Light source ø38mm (2 W led )  
Power LED Power (3W e )  
ø54mm (6W led ) Multichip  
Power Led

Power (5,8W led ) and (6,3W e )  
Power (6,3 W led ) and (6,9W e  
@230V), CRI ≥80, 3000K/  
4000K

outgoing rubber cable  
L.500mm suitable for external  
use with IP Heat-shrink tube  
connector for IP connection.

CLASS III,II

IP65

Accessories Tube Frame  
(90117-90127) Eyelid frame  
(90157-90167) connectors  
(9004-9005) and remote  
power supplies to be  
separately ordered.



3000K    Ø54    26°    5,8W<sub>led</sub>    6,3W<sub>e</sub>    264lm    24V

900412036

900412039



900422036

900422039

4000K    Ø54    26°    5,8W<sub>led</sub>    6,3W<sub>e</sub>    277lm    24V

