



DX

Ø54 - 26°



anodized
aluminium



anodized
bronze

Projector suitable for solid surfaces, wall or ceiling installation. Turned anodized aluminium

available in two sizes ø38mm and different height Sizes (h.60mm, h.160mm, h.500mm) or ø54mm and different height sizes (h.70mm, h.170mm, h.510mm) extremely versatile due to adjustability and low luminance.

Natural aluminium, Bronze and black (for accessories only) surface anodizing treatment.

Tempered silkscreened transparent glass, mechanically fixed with silicon glue, aluminium

Honeycomb.

Beams DX38 (18°;36°) DX54 (26°;52°)

Supply 24V remote power supply to be ordered, model DX54 also available operating 220-240V.

Light source ø38mm (2 W led)
Power LED Power (3W e)
ø54mm (6W led) Multichip
Power Led

Power (5,8W led) and (6,3W e)
Power (6,3 W led) and (6,9W e
@230V), CRI ≥80, 3000K/
4000K

outgoing rubber cable
L.500mm suitable for external
use with IP Heat-shrink tube
connector for IP connection.

CLASS III,II

IP65

Accessories Tube Frame
(90117-90127) Eyelid frame
(90157-90167) connectors
(9004-9005) and remote
power supplies to be
separately ordered.



3000K Ø54 26° 6W_{led} 6,9W_e 264lm 220-240V

900411006

900411009



900421006

900421009

4000K Ø54 26° 6W_{led} 6,9W_e 277lm 220-240V

