



DX STEM

Ø54 - 26° - h70/170/510mm



anodized
aluminium



anodized
bronze

Projector suitable for ground installation. Turned anodized aluminium available in two sizes $\varnothing 38$ mm heights (h.60mm, h.160mm, h.500mm) or $\varnothing 54$ (h.70mm, h.170mm, h.510mm), extremely versatile due to adjustability and low luminance.

Natural aluminium, Bronze and black (for accessories only) surface anodizing treatment.

Tempered silkscreened transparent glass, mechanically fixed with silicon glue, aluminium Honeycomb.

Beams DX38 (18°;36°) DX54 (26°;52°)

Supply 24V remote power supply to be ordered, model DX54 also available operating 220-240V.

Light source $\varnothing 38$ mm (2 W_{led})
Power LED Power (3W_e)
 $\varnothing 54$ mm (6W_{led}) Multichip
Power Led Power (5,8W_{led}) and
(6,3W_e) Power (6,3 W_{led}) and
(6,9W_e @230V), CRI ≥ 80 ,
3000K/4000K

outgoing rubber cable
L.1000mm suitable for external
use with IP Heat-shrink tube
connector for IP connection
and plastic spike.

CLASS III,I

IP65

Accessories Tube Frame
(90117-90157) Eyelid frame
(90127-90167) and remote
power supplies to be
separately ordered.



h70mm



3000K Ø54 26° 5,8W_{led} 6,3W_e 264lm 24V

900412116 900412119



900422116 900422119

4000K Ø54 26° 5,8W_{led} 6,3W_e 277lm 24V



h170mm



3000K Ø54 26° 5,8W_{led} 6,3W_e 264lm 24V

900412126 900412129



900422126 900422129

4000K Ø54 26° 5,8W_{led} 6,3W_e 277lm 24V

h510mm



3000K Ø54 26° 5,8W_{led} 6,3W_e 264lm 24V

900412136 900412139



900422136 900422139

4000K Ø54 26° 5,8W_{led} 6,3W_e 277lm 24V

