



DX STEM

Ø54 - 52° - h70/170/510mm



anodized
aluminium



anodized
bronze

Projector suitable for ground installation. Turned anodized aluminium available in two sizes \varnothing 38mm heights (h.60mm, h.160mm, h.500mm) or \varnothing 54 (h.70mm, h.170mm, h.510mm), extremely versatile due to adjustability and low luminance.

Natural aluminium, Bronze and black (for accessories only) surface anodizing treatment.

Tempered silkscreened transparent glass, mechanically fixed with silicon glue, aluminium Honeycomb.

Beams DX38 (18°;36°) DX54 (26°;52°)

Supply 24V remote power supply to be ordered, model DX54 also available operating 220-240V.

Light source \varnothing 38mm (2 W_{led})
Power LED Power (3W_e)
 \varnothing 54mm (6W_{led}) Multichip
Power Led Power (5,8W_{led}) and
(6,3W_e) Power (6,3 W_{led}) and
(6,9W_e @230V), CRI \geq 80,
3000K/4000K

outgoing rubber cable
L.1000mm suitable for external
use with IP Heat-shrink tube
connector for IP connection
and plastic spike.

CLASS III,I

IP65

Accessories Tube Frame
(90117-90157) Eyelid frame
(90127-90167) and remote
power supplies to be
separately ordered.



h70mm



3000K Ø54 52° 5,8W_{led} 6,3W_e 142lm 24V

900412146 900412149



900422146 900422149

4000K Ø54 52° 5,8W_{led} 6,3W_e 149lm 24V



h170mm



3000K Ø54 52° 5,8W_{led} 6,3W_e 142lm 24V

900412156 900412159



900422156 900422159

4000K Ø54 52° 5,8W_{led} 6,3W_e 149lm 24V



h510mm



3000K Ø54 52° 5,8W_{led} 6,3W_e 142lm 24V

900412166 900412169



900422166 900422169

4000K Ø54 52° 5,8W_{led} 6,3W_e 149lm 24V

