

ZERO

Ø65 52°



anodized
aluminium

Ground recessed or wall recessed available in three sizes (ø45mm - ø65mm - ø85mm), turned aluminium in Natural colour structure

aluminium Honeycomb.

Tempered silkscreened transparent glass mechanically fixed with silicon glue.

24Vdc supply, remote power supply to be separately ordered and 220-240V model only for ø85.

ø65mm 24V (5,8W led 6,3W e)
beam 52°

all fixtures come with multipoles rubber outgoing piece of cable L.200mm suitable for external use to be used for connection.

Light source

Power Led CRI≥80 3000K/
4000K













Mid Power (only for ø85 24dc)

CLASS III,

IP 67

plastic boxes (9001,9002,9003) mandatory for installation, IP connectors (9004,9005) remote power supplies to be separately ordered



Ø65 	3000K	Ø65 52°	5,8W _{led}	6,3W _e	142lm	24V	
	900112076						
	900122076						
honeycomb Ø65 	4000K	Ø65 52°	5,8W _{led}	6,3W _e	149lm	24V	
	900112066						
	900122066						
	3000K	Ø65 52°	5,8W _{led}	6,3W _e	142lm	24V	
	900112066						
	4000K	Ø65 52°	5,8W _{led}	6,3W _e	149lm	24V	