

ZERO

Ø85 diffused



anodized
aluminium

Ground recessed or wall recessed available in three sizes (ø45mm - ø65mm - ø85mm), turned aluminium in Natural colour structure

aluminium Honeycomb.

Tempered silkscreened transparent glass mechanically fixed with silicon glue.

24Vdc supply, remote power supply to be separately ordered and 220-240V model only for ø85.

Power ø45mm 24V (2W led 3W e) beam 36°

ø65mm 24V (5,8W led 6,3W e) beam 52°

ø85mm 24V (6,5W e,led) diffused

ø85mm 6,88W@230V

all fixtures come with multipoles rubber outgoing piece of cable L.200mm suitable for external use to be used for connection.

Light source

Power Led CRI≥80 3000K/4000K

Mid Power (only for ø85 24dc)

CLASS III, I(230V)

IP 67

plastic boxes (9001,9002,9003) mandatory for installation, IP connectors (9004,9005) remote power supplies to be separately ordered



Ø85



3000K Ø85 diffused 5,5W_{led} 131lm 24V

900112086



900122086

4000K Ø85 diffused 5,5W_{led} 137lm 24V



Ø85



3000K Ø85 diffused 6,7W 131lm 220-240V

900111006



900121006

4000K Ø85 diffused 6,7W 137lm 220-240V

