

# ZERO

Ø45 36°

Ø65 52°

Ø85 diffused



anodized  
aluminium

Ground recessed or wall recessed available in three sizes (Ø45mm - Ø65mm - Ø85mm), turned aluminium in Natural colour structure

aluminium Honeycomb.

Tempered silkscreened transparent glass mechanically fixed with silicon glue.

24Vdc supply, remote power supply to be separately ordered and 220-240V model only for Ø85.

Power Ø45mm 24V ( 2W led 3W e ) beam 36°

Ø65mm 24V (5,8W led 6,3W e ) beam 52°

Ø85mm 24V (6,5W e,led ) diffused

Ø85mm 6,88W@230V

all fixtures come with multipoles rubber outgoing piece of cable L.200mm suitable for external use to be used for connection.

Light source

Power Led CRI≥80 3000K/4000K

Mid Power ( only for Ø85 24dc)

CLASS III, I(230V)

IP 67

plastic boxes (9001,9002,9003) mandatory for installation, IP connectors (9004,9005) remote power supplies to be separately ordered

Ø45



3000K    Ø45 36°    2W<sub>led</sub>    3W<sub>e</sub>    103lm    24V

900112036



900122036

4000K    Ø45 36°    2W<sub>led</sub>    3W<sub>e</sub>    108lm    24V



honeycomb

Ø45





3000K    Ø45 36°    2W<sub>led</sub>    3W<sub>e</sub>    103lm    24V

900112026















900122026

4000K    Ø45 36°    2W<sub>led</sub>    3W<sub>e</sub>    108lm    24V





Ø65 	3000K	Ø65 52°	5,8W <sub>led</sub>	6,3W <sub>e</sub>	142lm	24V	    
	900112076						
	900122076						
honeycomb Ø65 	3000K	Ø65 52°	5,8W <sub>led</sub>	6,3W <sub>e</sub>	142lm	24V	  
	900112066						
	900122066						
	4000K	Ø65 52°	5,8W <sub>led</sub>	6,3W <sub>e</sub>	149lm	24V	





Ø85



3000K      Ø85      diffused      5,5W<sub>led</sub>      131lm      24V

900112086



900122086

4000K      Ø85      diffused      5,5W<sub>led</sub>      137lm      24V



Ø85





3000K      Ø85      diffused      6,7W      131lm      220-240V

900111006



900121006

4000K      Ø85      diffused      6,7W      137lm      220-240V





## ACCESSORIES

<b>RECESSED BOX Zero Ø45</b>		
	9001	
<b>RECESSED BOX Zero Ø65</b>		
	9002	
<b>RECESSED BOX Zero Ø85</b>		
	9003	
<b>3-4 WAY TERMINAL BLOCK IP68</b>		
	9005	
<b>POWER SUPPLY 16W 110-240V IP20</b>		
Dimensioni: 118x52x22mm	9006	
<b>POWER SUPPLY 20W 110-240V IP20</b>		
Dimensioni: 103x67x21mm	9007	
<b>POWER SUPPLY 50W 110-240V IP20</b>		
Dimensioni: 190x60x36mm	9008	

For the installation of recessed ground fixture, a proper drainage must be provided and the use installation box is mandatory.

Do not install in hollow areas or water flooding/stagnating areas, water should flow out within 30min. the use of IP connecting tools is warmly suggested to avoid water ingress.

We recommend the use of connecting tools that grant an IP degree equal or higher than the one declared for products .